



SS10



SS20



SS30


MODEL	HP/KW	RPM	CYLINDER	Bore/stroke (mm)	AIR DELIVERY L/MIN CFM	PRESSURE PSI/BAR	N.W Kg/Lbs	PACKAGING L x W x H
SS10	1/0.75	860	1	51/38	66.7/2.4	145/10	8.5/18	240x240x290
SS20	2/1.5	1180	1	65/46	180/6.4	145/10	14.2/31	280x280x380
SS30	3/2.2	1180	1	65/50	391/13.8	145/10	24.0/53	340x330x390



SB75



SB100



SB150

MODEL	HP/KW	RPM	CYLINDER	BORE/STROKE (mm)	AIR DELIVERY L/MIN CFM	PRESSURE PSI/BAR	N.W Kg/Lbs	PACKAGING L x W x H
SB75	7.5/5.6	850	3	80/60	768.8/27	145/10	59/130	(1200 x 1180 x 580) x 4
SB100	10.0/7.5	900	2	100/100	1413/498	145/10	134/295	(1460 x 1050 x 720) x 4
SB150	15.0/11	800	3	100/100	1884/66.5	145/10	138/304	(1460 x 1050 x 720) x 4



SB30



SB40



SB55

MODEL	HP/KW	RPM	CYLINDER	Bore/stroke (mm)	AIR DELIVERY L/MIN CFM	PRESSURE PSI/BAR	N.W Kg/Lbs	PACKAGING L x W x H
SB30	3.0/2.2	1800	2	65/46	549/19.4	145/10	25/55	400 x 300 x 360
SB40	4.0/3	1000	3	65/48	477/16.8	145/10	35/77	470 x 360 x 400
SB55	5.5/4	880	2	80/60	530/18.7	145/10	35/121	(1100 x 1080 x 550) x 6